

INSTALL TAPERED EDGE STRIP TO PROMOTE DRAINAGE INTO GUTTER AND TO PREVENT PONDING ALONG EDGE

SHEET METAL OR MEMBRANE COATED METAL EDGE FLASHING (AS REQUIRED BY MANUFACTURER)

SEALANT (IF REQUIRED BY THE SPECIFIC SYSTEM)

FLASHING MEMBRANE

FASTENERS AT APPROX. 3" O.C., DO NOT STAGGER

SINGLE PLY ROOF MEMBRANE OVER SPECIFIED RECOVERY BOARD

EXIST. INSULATION

CONTINUOUS CLEAT

GUTTER SPACER ALTERNATELY SPACED FROM BRACKETS

OPTIONAL: TURN-DOWN

SHEET METAL GUTTER

EXIST. ROOF DECK

NEW WOOD NAILER

EXIST. ROOF MEMBRANE

CONTINUOUS SHEET METAL CLOSURE FASTENED APPROX. 18" O.C.

EXTEND FIELD SHEET OR A SEPARATE MEMBRANE SHEET TO OVERLAY METAL CLOSURE

GUTTER BRACKET SUPPORT AT 12" TO 36" O.C. DEPENDING UPON CONDITIONS

A
04

GUTTER

PROJECT TITLE :

ROOF RECOVERY
2024

CIRE Equity
Produce Row
Houston, TX

JOB NO,

DRAWN BY :

CHECKED

SCALE

DATE

Jan. 25, 2024

CAD FILE

SHEET

DRAWING NO.

d004